## 40 CFR Ch. I (7-1-10 Edition)

Control device	Parameters to be monitored <sup>a</sup>	Recordkeeping and reporting requirements for monitored parameters
Carbon adsorber h	Total regeneration stream mass or volumetric or volumetric flow during carbon bed regeneration cycle(s) [63.127(b)(3)], and.	Record of total regeneration stream mass or volumetric flow for each carbon bed regeneration cycle.     Record and report the total regeneration stream mass or volumetric flow during each carbon bed regeneration cycle during the period of the performance test—NCS.     Report all carbon bed regeneration cycles when the total regeneration stream mass or volumetric flow is outside the range established in the NCS or operating permit and all operating days when insufficient monitoring data are collected —PR.
	Temperature of the carbon bed	1. Records of the temperature of the carbon bed after each regen-
	after regeneration [and within 15 minutes of completing any cooling cycle(s)] [63.127(b)(3)].	eration.  2. Record and report the temperature of the carbon bed after each regeneration during the period of the performance test—NCS.  3. Report all the carbon bed regeneration cycles during which the temperature of the carbon bed after regeneration is outside the range established in the NCS or operating permit and all operating days when insufficient monitoring data are collected —PR.
All recovery devices (as an alternative to the above).	Concentration level or reading in- dicated by an organic moni- toring device at the outlet of the recovery device [63.127(b)].	Continuous records during loading.     Record and report the concentration level or reading averaged over the full period of the performance test—NCS.
	(,)	Record the daily average concentration level or reading for each operating day.
		Report all daily average concentration levels or readings that are outside the range established in the NCS or operating permit and all operating days when insufficient monitoring data are collected —PR.
All control devices and vapor balancing systems.	Presence of flow diverted to the atmosphere from the control device [63.127(d)(1)] or.	Hourly records of whether the flow indicator was operating and whether a diversion was detected at any time during each hour.
		<ol><li>Record and report the duration of all periods when the vent stream is diverted through a bypass line or the monitor is not operating—PR.</li></ol>
	Monthly inspections of sealed valves [63.127(d)(2)].	Records that monthly inspections were performed.     Record and report all monthly inspections that show the valves are moved to the diverting position or the seal has been changed.

TABLE 8 TO SUBPART G OF PART 63—OR-GANIC HAP'S SUBJECT TO THE WASTEWATER PROVISIONS FOR PROC-ESS UNITS AT NEW SOURCES

Chemical name	CAS No. a	
Allyl chloride	107051	
Benzene	71432	
Butadiene (1,3-)	106990	
Carbon disulfide	75150	
Carbon tetrachloride	56235	
Cumene	98828	
Ethylbenzene	100414	
Ethyl chloride (Chloroethane)	75003	
Ethylidene dichloride	75343	
(1,1-Dichloroethane).		
Hexachlorobutadiene	87683	
Hexachloroethane	6772	
Hexane	100543	

Chemical name	CAS No. a	
Methyl bromide (Bromomethane)	74839	
Methyl chloride (Chloromethane)	74873	
Phosgene	75445	
Tetrachloroethylene (Perchloroethylene)	127184	
Toluene	108883	
Trichloroethane (1,1,1-) (Methyl chloroform)	71556	
Trichloroethylene	79016	
Trimethylpentane (2,2,4-)	540841	
Vinyl chloride (chloroethylene)	75014	
Vinylidene chloride	75354	
(1,1-Dichloroethylene).		
Xylene (m-)	108383	
Xylene (p-)	106423	

<sup>&</sup>lt;sup>a</sup>CAS numbers refer to the Chemical Abstracts Service registry number assigned to specific compounds, isomers, or mixtures of compounds.

NOTE. The list of organic HAP's on table 8 is a subset of the list of organic HAP's on table 9 of this subpart.

a Regulatory citations are listed in brackets.

b Monitor may be installed in the firebox or in the ductwork immediately downstream of the firebox before any substantial heat exchange is encountered.

c "Continuous records" is defined in § 63.111 of this subpart.

d NCS = Notification of Compliance Status described in § 63.152 of this subpart.

The daily average is the average of all recorded parameter values for the operating day. If all recorded values during an operating day are within the range established in the NCS or operating permit, a statement to this effect can be recorded instead of the daily average.

The periodic reports shall include the duration of periods when monitoring data are not collected for each excursion as defined in § 63.152(c)(2)(ii)(A) of this subpart.

PR = Periodic Reports described in § 63.152 of this subpart.

hAlternatively, these devices may comply with the organic monitoring device provisions listed at the end of this table under "All Recovery Devices."